LR1000D23 · 905 NM

CLASS-1 D SERIES

LR1000D23

LASER CLASS
CLASS 1
IEC 60825-1

Compact Ø23 × 47 mm Class-1 ranging module — 4–1,000 m (vegetation ⩾ 750 m, max 1,200 m at night) with IP67 lens cavity, for handheld and mounted electro-optical systems.

MAX RANGE	ACCURACY	WEIGHT	INTERFACE
4–1,000 m (max 1,200 m)	**±1 m**	**≈ 20 g**	**UART-TTL**

TECHNICAL SPECIFICATIONS — FULL SHEET

Laser wavelength	905 nm ± 5 nm
Laser beam divergence	< 6 mrad
Optical material	Resin aspheric lens
Receiver aperture	20 mm ± 0.05 mm
Ranging range	White building: 4–1,000 m (max 1,200 m at night) · vegetation ⩾ 750 m
Ranging accuracy	δ ⩽ 100 cm, 5 ⩽ d < 1,000 m (standard version ±1 m)
Ranging frequency	3–12 Hz (customizable)
Ranging resolution	20 cm typical
Valid measurement rate	⩾ 98%
False alarm rate	⩽ 1%
Interface	UART-TTL (customizable)
Baud rate	115200 bps
Supply voltage	3.3–5 V (recommended ⩾ 3.5 V)
Operating power	Average < 1 W
Average laser power	On request
Response time	On request
Peak / inrush current	≈ 350 mA @ 3.3 V typical
Operating temperature	-20 to +60 ℃
Storage temperature	-40 to +60 ℃
Protection rating	Lens cavity IP67
Laser safety class	IEC Class 1
Dimensions	Ø23 mm × 47 mm
Spot banding	3.15 × 3.15 cm @ 10 m
Weight	≈ 20 g
Shock / vibration	1000 g/ms (10×/s along optical axis) · 5–50–5 Hz, 2.5 g (also rated 1000 g, 1 ms, 500 cycles)
Reliability	MTBF ⩾ 1500 h



INTERFACE — UART-TTL

PIN	SIGNAL	DESCRIPTION
1	GND	Power –
2	VCC	Power +
3	I/O	Reserved for expansion
4	TXD	Module → host
5	RXD	Host → module
6	SW-SHOT	Function enable (active high)

APPLICATION FIT

HANDHELD OPTICS · SECURITY · INDUSTRIAL

Standard 8-byte UART frame (0x55 0xAA header, function code, 4 data bytes, checksum); distance returned ×10 for a one-decimal reading. Full integration manual ships with samples.

ERDI TECH LTD — 905 nm eye-safe laser rangefinder modules (IEC 60825-1 Class 1)
Email: **tommy@erdimail.com** · WhatsApp: **+86 133 0819 5790** (https://wa.me/8613308195790) · Tel: +86 133 0819 5790
Web: **https://erdilrf.com** · Room 2812, 28/F, Building 3, No. 88 Jiaozi Avenue, Chengdu Hi-Tech Zone, Sichuan, China